

Permit to Construct



R13- 3208

This permit is issued in accordance with the West Virginia Air Pollution Control Act (West Virginia Code §§22-5-1 et seq.) and 45 C.S.R. 13 – Permits for Construction, Modification, Relocation and Operation of Stationary Sources of Air Pollutants, Notification Requirements, Temporary Permits, General Permits and Procedures for Evaluation. The permittee identified at the above-referenced facility is authorized to construct the stationary sources of air pollutants identified herein in accordance with all terms and conditions of this permit.

Issued to:

Cone Midstream Partners, LP
Oxford Station
017-00102

William F. Durham
Director

Issued: Draft • Effective: Draft

Facility Location: West Union, Doddridge County, West Virginia
Mailing Address: 1000 Consol Energy Drive, Canonsburg, PA 15321
Facility Description: Natural gas dehydration station
NAICS Codes: 486210
UTM Coordinates: 515.469 km Easting • 4,343.705 km Northing • Zone 17
Permit Type: Construction
Description of Change: Installation and operation of a natural gas dehydration station.

Any person whose interest may be affected, including, but not necessarily limited to, the applicant and any person who participated in the public comment process, by a permit issued, modified or denied by the Secretary may appeal such action of the Secretary to the Air Quality Board pursuant to article one [§§22B-1-1 et seq.], Chapter 22B of the Code of West Virginia. West Virginia Code §§22-5-14.

The source is not subject to 45CSR30.

Table of Contents

1.0.	Emission Units	5
1.1.	Control Devices.....	5
2.0.	General Conditions.....	6
2.1.	Definitions	6
2.2.	Acronyms.....	6
2.3.	Authority.....	7
2.4.	Term and Renewal	7
2.5.	Duty to Comply	7
2.6.	Duty to Provide Information	7
2.7.	Duty to Supplement and Correct Information.....	8
2.8.	Administrative Update	8
2.9.	Permit Modification.....	8
2.10.	Major Permit Modification	8
2.11.	Inspection and Entry	8
2.12.	Emergency	8
2.13.	Need to Halt or Reduce Activity Not a Defense.....	9
2.14.	Suspension of Activities	9
2.15.	Property Rights	9
2.16.	Severability	10
2.17.	Transferability.....	10
2.18.	Notification Requirements	10
2.19.	Credible Evidence.....	10
3.0.	Facility-Wide Requirements.....	11
3.1.	Limitations and Standards	11
3.2.	Monitoring Requirements	11
3.3.	Testing Requirements	11
3.4.	Recordkeeping Requirements	13
3.5.	Reporting Requirements	13
4.0.	Source-Specific Requirements.....	15
4.1.	Limitations and Standards	15
5.0.	Source-Specific Requirements (Emergency Generator, VS-3).....	17
5.1.	Limitations and Standards	17
5.2.	Testing Requirements	17
5.3.	Recordkeeping Requirements	17
5.4.	Reporting Requirements	18
6.0.	Source-Specific Hazardous Air Pollutant Requirements (Natural Gas Dehydration Unit (VS-2) Not Subject to MACT Standards and being controlled by an Enclosed Combustor (CMB-1))	19
6.1.	Limitations and Standards	19
6.2.	Monitoring Requirements	20
6.3.	Testing Requirements	20
6.4.	Recordkeeping Requirements	21
6.5.	Reporting Requirements	22

7.0.	Source-Specific Requirements (Reboiler (VS-1))	23
7.1.	Limitations and Standards	23
7.2.	Monitoring Requirements	23
7.3.	Testing Requirements	23
7.4.	Recordkeeping Requirements	23
7.5.	Reporting Requirements	23
8.0.	Source-Specific Requirements (Produced Fluids Tank, Tank-1)	24
8.1.	Limitations and Standards	24
8.2.	Monitoring Requirements	25
8.3.	Recordkeeping Requirements	26
8.4.	Reporting Requirements	28
9.0.	Source-Specific Requirements (Product Loadout Rack, BL-1)	29
9.1.	Limitations and Standards	29
9.2.	Monitoring Requirements	30
9.3.	Recordkeeping Requirements	31
9.4.	Reporting Requirements	33
	CERTIFICATION OF DATA ACCURACY.....	34

1.0. Emission Units

Emission Unit ID	Emission Point ID	Emission Unit Description	Year Installed	Design Capacity	Control Device
Tank-1	VDU-1	Produced Fluids Storage Tank	2014	6,000 gallons	VDU-1
VDU-1	VDU-1	Vapor Destruction Unit	2014	9.21 MMBTU/hr	None
SV-1	CMB-1	Glycol Dehydration Unit Still Vent	2014	50 mmscfd	CMB-1
BLR-1	VS-1	Glycol Dehydration Unit Reboiler	2014	1 MMBTU/hr	None
EG-1	VS-3	Cummins Emergency Generator	2014	324 HP	None
CMB-1	CMB-1	Enclosed Vapor Combustor	2014	6 MMBTU/hr	None
BL-1	VDU-1	Liquids Unloading	2014	2,649 gal/yr	VDU-1

1.1. Control Devices

Emission Unit	Pollutant	Control Device	Control Efficiency
50 mmscfd TEG Dehydrator Still Vent (SV-1)	Volatile Organic Compounds	Enclosed Combustion Device (CMB-1)	98 %
	Hazardous Air Pollutants		98 %
Produced Fluids Storage Tank (Tank1)	Volatile Organic Compounds	Vapor Destruction Unit	95 %
	Hazardous Air Pollutants		95 %
Liquids Loading Rack (BL-1)	Volatile Organic Compounds	Vapor Destruction Unit	95 %
	Hazardous Air Pollutants		95 %

2.0. General Conditions

2.1. Definitions

- 2.1.1. All references to the “West Virginia Air Pollution Control Act” or the “Air Pollution Control Act” mean those provisions contained in W.Va. Code §§ 22-5-1 to 22-5-18.
- 2.1.2. The “Clean Air Act” means those provisions contained in 42 U.S.C. §§ 7401 to 7671q, and regulations promulgated thereunder.
- 2.1.3. “Secretary” means the Secretary of the Department of Environmental Protection or such other person to whom the Secretary has delegated authority or duties pursuant to W.Va. Code §§ 22-1-6 or 22-1-8 (45CSR§30-2.12.). The Director of the Division of Air Quality is the Secretary’s designated representative for the purposes of this permit.

2.2. Acronyms

CAAA	Clean Air Act Amendments	NO_x	Nitrogen Oxides
CBI	Confidential Business Information	NSPS	New Source Performance Standards
CEM	Continuous Emission Monitor	PM	Particulate Matter
CES	Certified Emission Statement	PM_{2.5}	Particulate Matter less than 2.5 µm in diameter
C.F.R. or CFR	Code of Federal Regulations	PM₁₀	Particulate Matter less than 10µm in diameter
CO	Carbon Monoxide	Ppb	Pounds per Batch
C.S.R. or CSR	Codes of State Rules	Pph	Pounds per Hour
DAQ	Division of Air Quality	Ppm	Parts per Million
DEP	Department of Environmental Protection	Ppm_v or ppmv	Parts per Million by Volume
dscm	Dry Standard Cubic Meter	PSD	Prevention of Significant Deterioration
FOIA	Freedom of Information Act	Psi	Pounds per Square Inch
HAP	Hazardous Air Pollutant	SIC	Standard Industrial Classification
HON	Hazardous Organic NESHAP	SIP	State Implementation Plan
HP	Horsepower	SO₂	Sulfur Dioxide
lbs/hr	Pounds per Hour	TAP	Toxic Air Pollutant
LDAR	Leak Detection and Repair	TPY	Tons per Year
M	Thousand	TRS	Total Reduced Sulfur
MACT	Maximum Achievable Control Technology	TSP	Total Suspended Particulate
MDHI	Maximum Design Heat Input	USEPA	United States Environmental Protection Agency
MM	Million	UTM	Universal Transverse Mercator
MMBtu/hr or mmbtu/hr	Million British Thermal Units per Hour	VEE	Visual Emissions Evaluation
MMCF/hr or mmcf/hr	Million Cubic Feet per Hour	VOC	Volatile Organic Compounds
NA	Not Applicable	VOL	Volatile Organic Liquids
NAAQS	National Ambient Air Quality Standards		
NESHAPS	National Emissions Standards for Hazardous Air Pollutants		

2.3. Authority

This permit is issued in accordance with West Virginia air pollution control law W.Va. Code §§ 22-5-1. et seq. and the following Legislative Rules promulgated thereunder:

- 2.3.1. 45CSR13 – *Permits for Construction, Modification, Relocation and Operation of Stationary Sources of Air Pollutants, Notification Requirements, Temporary Permits, General Permits and Procedures for Evaluation*;

2.4. Term and Renewal

- 2.4.1. This Permit shall remain valid, continuous and in effect unless it is revised, suspended, revoked or otherwise changed under an applicable provision of 45CSR13 or any other applicable legislative rule;

2.5. Duty to Comply

- 2.5.1. The permitted facility shall be constructed and operated in accordance with the plans and specifications filed in Permit Applications R13-3208 and any modifications, administrative updates, or amendments thereto. The Secretary may suspend or revoke a permit if the plans and specifications upon which the approval was based are not adhered to;
[45CSR§§13-5.11 and -10.3.]
- 2.5.2. The permittee must comply with all conditions of this permit. Any permit noncompliance constitutes a violation of the West Virginia Code and the Clean Air Act and is grounds for enforcement action by the Secretary or USEPA;
- 2.5.3. Violations of any of the conditions contained in this permit, or incorporated herein by reference, may subject the permittee to civil and/or criminal penalties for each violation and further action or remedies as provided by West Virginia Code 22-5-6 and 22-5-7;
- 2.5.4. Approval of this permit does not relieve the permittee herein of the responsibility to apply for and obtain all other permits, licenses, and/or approvals from other agencies; i.e., local, state, and federal, which may have jurisdiction over the construction and/or operation of the source(s) and/or facility herein permitted.

2.6. Duty to Provide Information

The permittee shall furnish to the Secretary within a reasonable time any information the Secretary may request in writing to determine whether cause exists for administratively updating, modifying, revoking, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the Secretary copies of records to be kept by the permittee. For information claimed to be confidential, the permittee shall furnish such records to the Secretary along with a claim of confidentiality in accordance with 45CSR31. If confidential information is to be sent to USEPA, the permittee shall directly provide such information to USEPA along with a claim of confidentiality in accordance with 40 C.F.R. Part 2.

2.7. Duty to Supplement and Correct Information

Upon becoming aware of a failure to submit any relevant facts or a submittal of incorrect information in any permit application, the permittee shall promptly submit to the Secretary such supplemental facts or corrected information.

2.8. Administrative Update

The permittee may request an administrative update to this permit as defined in and according to the procedures specified in 45CSR13.

[45CSR§13-4.]

2.9. Permit Modification

The permittee may request a minor modification to this permit as defined in and according to the procedures specified in 45CSR13.

[45CSR§13-5.4.]

2.10 Major Permit Modification

The permittee may request a major modification as defined in and according to the procedures specified in 45CSR14 or 45CSR19, as appropriate.

[45CSR§13-5.1]

2.11. Inspection and Entry

The permittee shall allow any authorized representative of the Secretary, upon the presentation of credentials and other documents as may be required by law, to perform the following:

- a. At all reasonable times (including all times in which the facility is in operation) enter upon the permittee's premises where a source is located or emissions related activity is conducted, or where records must be kept under the conditions of this permit;
- b. Have access to and copy, at reasonable times, any records that must be kept under the conditions of this permit;
- c. Inspect at reasonable times (including all times in which the facility is in operation) any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under the permit;
- d. Sample or monitor at reasonable times substances or parameters to determine compliance with the permit or applicable requirements or ascertain the amounts and types of air pollutants discharged.

2.12. Emergency

- 2.12.1. An "emergency" means any situation arising from sudden and reasonable unforeseeable events beyond the control of the source, including acts of God, which situation requires immediate corrective action to restore normal operation, and that causes the source to exceed a technology-based emission limitation under the permit, due to unavoidable increases in emissions attributable to the emergency. An emergency shall not include noncompliance to the extent caused by

improperly designed equipment, lack of preventative maintenance, careless or improper operation, or operator error.

- 2.12.2. Effect of any emergency. An emergency constitutes an affirmative defense to an action brought for noncompliance with such technology-based emission limitations if the conditions of Section 2.12.3 are met.
- 2.12.3. The affirmative defense of emergency shall be demonstrated through properly signed, contemporaneous operating logs, or other relevant evidence that:
 - a. An emergency occurred and that the permittee can identify the cause(s) of the emergency;
 - b. The permitted facility was at the time being properly operated;
 - c. During the period of the emergency the permittee took all reasonable steps to minimize levels of emissions that exceeded the emission standards, or other requirements in the permit; and
 - d. The permittee submitted notice of the emergency to the Secretary within one (1) working day of the time when emission limitations were exceeded due to the emergency and made a request for variance, and as applicable rules provide. This notice must contain a detailed description of the emergency, any steps taken to mitigate emissions, and corrective actions taken.
- 2.12.4. In any enforcement proceeding, the permittee seeking to establish the occurrence of an emergency has the burden of proof.
- 2.12.5. The provisions of this section are in addition to any emergency or upset provision contained in any applicable requirement.

2.13. Need to Halt or Reduce Activity Not a Defense

It shall not be a defense for a permittee in an enforcement action that it should have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit. However, nothing in this paragraph shall be construed as precluding consideration of a need to halt or reduce activity as a mitigating factor in determining penalties for noncompliance if the health, safety, or environmental impacts of halting or reducing operations would be more serious than the impacts of continued operations.

2.14. Suspension of Activities

In the event the permittee should deem it necessary to suspend, for a period in excess of sixty (60) consecutive calendar days, the operations authorized by this permit, the permittee shall notify the Secretary, in writing, within two (2) calendar weeks of the passing of the sixtieth (60) day of the suspension period.

2.15. Property Rights

This permit does not convey any property rights of any sort or any exclusive privilege.

2.16. Severability

The provisions of this permit are severable and should any provision(s) be declared by a court of competent jurisdiction to be invalid or unenforceable, all other provisions shall remain in full force and effect.

2.17. Transferability

This permit is transferable in accordance with the requirements outlined in Section 10.1 of 45CSR13. [45CSR§13-10.1.]

2.18. Notification Requirements

The permittee shall notify the Secretary, in writing, no later than thirty (30) calendar days after the actual startup of the operations authorized under this permit.

2.19. Credible Evidence

Nothing in this permit shall alter or affect the ability of any person to establish compliance with, or a violation of, any applicable requirement through the use of credible evidence to the extent authorized by law. Nothing in this permit shall be construed to waive any defense otherwise available to the permittee including, but not limited to, any challenge to the credible evidence rule in the context of any future proceeding.

3.0. Facility-Wide Requirements

3.1. Limitations and Standards

- 3.1.1. **Open burning.** The open burning of refuse by any person is prohibited except as noted in 45CSR§6-3.1.
[45CSR§6-3.1.]
- 3.1.2. **Open burning exemptions.** The exemptions listed in 45CSR§6-3.1 are subject to the following stipulation: Upon notification by the Secretary, no person shall cause or allow any form of open burning during existing or predicted periods of atmospheric stagnation. Notification shall be made by such means as the Secretary may deem necessary and feasible.
[45CSR§6-3.2.]
- 3.1.3. **Asbestos.** The permittee is responsible for thoroughly inspecting the facility, or part of the facility, prior to commencement of demolition or renovation for the presence of asbestos and complying with 40 C.F.R. § 61.145, 40 C.F.R. § 61.148, and 40 C.F.R. § 61.150. The permittee, owner, or operator must notify the Secretary at least ten (10) working days prior to the commencement of any asbestos removal on the forms prescribed by the Secretary if the permittee is subject to the notification requirements of 40 C.F.R. § 61.145(b)(3)(i). The USEPA, the Division of Waste Management, and the Bureau for Public Health - Environmental Health require a copy of this notice to be sent to them.
[40CFR§61.145(b) and 45CSR§34]
- 3.1.4. **Odor.** No person shall cause, suffer, allow or permit the discharge of air pollutants which cause or contribute to an objectionable odor at any location occupied by the public.
[45CSR§4-3.1] *[State Enforceable Only]*
- 3.1.5. **Permanent shutdown.** A source which has not operated at least 500 hours in one 12-month period within the previous five (5) year time period may be considered permanently shutdown, unless such source can provide to the Secretary, with reasonable specificity, information to the contrary. All permits may be modified or revoked and/or reapplication or application for new permits may be required for any source determined to be permanently shutdown.
[45CSR§13-10.5.]
- 3.1.6. **Standby plan for reducing emissions.** When requested by the Secretary, the permittee shall prepare standby plans for reducing the emissions of air pollutants in accordance with the objectives set forth in Tables I, II, and III of 45CSR11.
[45CSR§11-5.2.]

3.2. Monitoring Requirements

[Reserved]

3.3. Testing Requirements

- 3.3.1. **Stack testing.** As per provisions set forth in this permit or as otherwise required by the Secretary, in accordance with the West Virginia Code, underlying regulations, permits and orders, the permittee shall conduct test(s) to determine compliance with the emission limitations set forth in this permit and/or established or set forth in underlying documents. The Secretary, or his duly authorized representative, may at his option witness or conduct such test(s). Should the Secretary exercise his option to conduct such test(s), the operator shall provide all necessary sampling connections and sampling ports to be located in such manner as the Secretary may require, power

for test equipment and the required safety equipment, such as scaffolding, railings and ladders, to comply with generally accepted good safety practices. Such tests shall be conducted in accordance with the methods and procedures set forth in this permit or as otherwise approved or specified by the Secretary in accordance with the following:

- a. The Secretary may on a source-specific basis approve or specify additional testing or alternative testing to the test methods specified in the permit for demonstrating compliance with 40 C.F.R. Parts 60, 61, and 63 in accordance with the Secretary's delegated authority and any established equivalency determination methods which are applicable. If a testing method is specified or approved which effectively replaces a test method specified in the permit, the permit may be revised in accordance with 45CSR§13-4. or 45CSR§13-5.4 as applicable.
- b. The Secretary may on a source-specific basis approve or specify additional testing or alternative testing to the test methods specified in the permit for demonstrating compliance with applicable requirements which do not involve federal delegation. In specifying or approving such alternative testing to the test methods, the Secretary, to the extent possible, shall utilize the same equivalency criteria as would be used in approving such changes under Section 3.3.1.a. of this permit. If a testing method is specified or approved which effectively replaces a test method specified in the permit, the permit may be revised in accordance with 45CSR§13-4. or 45CSR§13-5.4 as applicable.
- c. All periodic tests to determine mass emission limits from or air pollutant concentrations in discharge stacks and such other tests as specified in this permit shall be conducted in accordance with an approved test protocol. Unless previously approved, such protocols shall be submitted to the Secretary in writing at least thirty (30) days prior to any testing and shall contain the information set forth by the Secretary. In addition, the permittee shall notify the Secretary at least fifteen (15) days prior to any testing so the Secretary may have the opportunity to observe such tests. This notification shall include the actual date and time during which the test will be conducted and, if appropriate, verification that the tests will fully conform to a referenced protocol previously approved by the Secretary.
- d. The permittee shall submit a report of the results of the stack test within sixty (60) days of completion of the test. The test report shall provide the information necessary to document the objectives of the test and to determine whether proper procedures were used to accomplish these objectives. The report shall include the following: the certification described in paragraph 3.5.1.; a statement of compliance status, also signed by a responsible official; and, a summary of conditions which form the basis for the compliance status evaluation. The summary of conditions shall include the following:
 1. The permit or rule evaluated, with the citation number and language;
 2. The result of the test for each permit or rule condition; and,
 3. A statement of compliance or noncompliance with each permit or rule condition.

[WV Code § 22-5-4(a)(14-15) and 45CSR13]

3.4. Recordkeeping Requirements

- 3.4.1. **Retention of records.** The permittee shall maintain records of all information (including monitoring data, support information, reports, and notifications) required by this permit recorded in a form suitable and readily available for expeditious inspection and review. Support information includes all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation. The files shall be maintained for at least five (5) years following the date of each occurrence, measurement, maintenance, corrective action, report, or record. At a minimum, the most recent two (2) years of data shall be maintained on site. The remaining three (3) years of data may be maintained off site, but must remain accessible within a reasonable time. Where appropriate, the permittee may maintain records electronically (on a computer, on computer floppy disks, CDs, DVDs, or magnetic tape disks), on microfilm, or on microfiche.
- 3.4.2. **Odors.** For the purposes of 45CSR4, the permittee shall maintain a record of all odor complaints received, any investigation performed in response to such a complaint, and any responsive action(s) taken.
[45CSR§4. State Enforceable Only.]

3.5. Reporting Requirements

- 3.5.1. **Responsible official.** Any application form, report, or compliance certification required by this permit to be submitted to the DAQ and/or USEPA shall contain a certification by the responsible official that states that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.
- 3.5.2. **Confidential information.** A permittee may request confidential treatment for the submission of reporting required by this permit pursuant to the limitations and procedures of W.Va. Code § 22-5-10 and 45CSR31.
- 3.5.3. **Correspondence.** All notices, requests, demands, submissions and other communications required or permitted to be made to the Secretary of DEP and/or USEPA shall be made in writing and shall be deemed to have been duly given when delivered by hand, or mailed first class with postage prepaid to the address(es) set forth below or to such other person or address as the Secretary of the Department of Environmental Protection may designate:

If to the DAQ:

Director
WVDEP
Division of Air Quality
601 57th Street SE
Charleston, WV 25304-2345

If to the US EPA:

Associate Director
Office of Air Enforcement and Compliance
Assistance
(3AP20)
U.S. Environmental Protection Agency
Region III
1650 Arch Street
Philadelphia, PA 19103-2029

3.5.4. Operating Fee

- 3.5.4.1. In accordance with 45CSR22 – Air Quality Management Fee Program, the permittee shall not operate nor cause to operate the permitted facility or other associated facilities on the same or contiguous sites comprising the plant without first obtaining and having in current effect a

Certificate to Operate (CTO). Such Certificate to Operate (CTO) shall be renewed annually, shall be maintained on the premises for which the certificate has been issued, and shall be made immediately available for inspection by the Secretary or his/her duly authorized representative.

- 3.5.4.2. In accordance with 45CSR22 – Air Quality Management Fee Program, enclosed with this permit is an Application for a Certificate to Operate (CTO). The CTO will cover the time period beginning with the date of initial startup through the following June 30. Said application and the appropriate fee shall be submitted to this office prior to the date of initial startup. For any startup date other than July 1, the permittee shall pay a fee or prorated fee in accordance with Section 4.5 of 45CSR22. A copy of this schedule may be found on the reverse side of the CTO application.
- 3.5.5. **Emission inventory.** At such time(s) as the Secretary may designate, the permittee herein shall prepare and submit an emission inventory for the previous year, addressing the emissions from the facility and/or process(es) authorized herein, in accordance with the emission inventory submittal requirements of the Division of Air Quality. After the initial submittal, the Secretary may, based upon the type and quantity of the pollutants emitted, establish a frequency other than on an annual basis.

4.0. Source-Specific Requirements

4.1. Limitations and Standards

- 4.1.1. **Record of Monitoring.** The permittee shall keep records of monitoring information that include the following:
- a. The date, place as defined in this permit, and time of sampling or measurements;
 - b. The date(s) analyses were performed;
 - c. The company or entity that performed the analyses;
 - d. The analytical techniques or methods used;
 - e. The results of the analyses; and
 - f. The operating conditions existing at the time of sampling or measurement.
- 4.1.2. **Minor Source of Hazardous Air Pollutants (HAP).** HAP emissions from the facility shall be less than 10 tons/year of any single HAP or 25 tons/year of any combination of HAPs. Compliance with this Section shall ensure that the facility is a minor HAP source.
- 4.1.3. **Operation and Maintenance of Air Pollution Control Equipment.** The permittee shall, to the extent practicable, install, maintain, and operate all pollution control equipment listed in Section 1.0 and associated monitoring equipment in a manner consistent with safety and good air pollution control practices for minimizing emissions, or comply with any more stringent limits set forth in this permit or as set forth by any State rule, Federal regulation, or alternative control plan approved by the Secretary.
[45CSR§13-5.11.]
- 4.1.4. **Record of Malfunctions of Air Pollution Control Equipment.** For all air pollution control equipment listed in Section 1.0, the permittee shall maintain records of the occurrence and duration of any malfunction or operational shutdown of the air pollution control equipment during which excess emissions occur. For each such case, the following information shall be recorded:
- a. The equipment involved.
 - b. Steps taken to minimize emissions during the event.
 - c. The duration of the event.
 - d. The estimated increase in emissions during the event.
- For each such case associated with an equipment malfunction, the additional information shall also be recorded:
- e. The cause of the malfunction.
 - f. Steps taken to correct the malfunction.
 - g. Any changes or modifications to equipment or procedures that would help prevent future recurrences of the malfunction.
- 4.1.5. The permittee shall install, maintain, and operate all above-ground piping, valves, pumps, etc. that service lines in the transport of potential sources of regulated air pollutants to prevent any substantive fugitive escape of regulated air pollutants. Any above-ground piping, valves, pumps, etc. that shows signs of excess wear and that have a reasonable potential for substantive fugitive emissions of regulated air pollutants shall be replaced.
- 4.1.6. If any leak is detected, the permittee shall repair the leak as soon as possible. The first attempt at repair must be made within five (5) days of discovering the leak, and the final repair must be made within 15 days of discovering the leak. The permittee shall record each leak detected and the associated repair. If reoccurring leaks are detected at sources specified in 4.1.5, then fugitive

emission monitoring shall be conducted at a minimum of quarterly, and may consist of Method 21, infrared camera, audio-visual-olfactory (AVO) inspections, or some combination thereof and must be approved by the Director. A proposed LDAR Protocol consisting of only AVO inspections will not be accepted by the Director. If no leaks are detected for four (4) consecutive quarters then the monitoring may return to only AVO inspections on an as needed basis.
[45CSR§13-5.11.]

DRAFT

5.0. Source-Specific Requirements (Emergency Generator, VS-3)

5.1. Limitations and Standards

- 5.1.1. Maximum emissions from the 324 hp diesel fired emergency generator, Cummins 100 DSGAA (VS-3) shall not exceed the following limits:

Pollutant	Maximum Hourly Emissions (lb/hr)	Maximum Annual Emissions (ton/year)
Nitrogen Oxides	1.78	0.45
Carbon Monoxide	0.50	0.12
Volatile Organic Compounds	0.36	0.09
Formaldehyde	0.15	0.04

- 5.1.2. **Maximum Yearly Operation Limitation.** The maximum yearly hours of operation for the emergency generator (VS-3) shall not exceed 500 hours per year. Compliance with the Maximum Yearly Operation Limitation shall be determined using a twelve (12) month rolling total. A twelve (12) month rolling total shall mean the sum of the hours of operation at any given time during the previous twelve (12) consecutive calendar months.
- 5.1.3. The permittee shall comply with all applicable emission standard requirements under NSPS for Stationary Compression Ignition Internal Combustion Engines specified in 40 CFR Part 60, Subpart IIII, and the National Emission Standards for Hazardous Air Pollutants (NESHAP) for Stationary Compression Ignition Internal Combustion Engines specified in 40 CFR Part 63, Subpart ZZZZ.

5.2. Testing Requirements

- 5.2.1. See Facility-Wide Testing Requirements Section 3.3 and all applicable testing requirements under NSPS for Stationary Compression Ignition Internal Combustion Engines specified in 40 CFR Part 60, Subpart IIII, and the National Emission Standards for Hazardous Air Pollutants (NESHAP) for Stationary Compression Ignition Internal Combustion Engines specified in 40 CFR Part 63, Subpart ZZZZ.

5.3. Recordkeeping Requirements

- 5.3.1. To demonstrate compliance with section 5.1.1 and 5.1.2, the permittee shall maintain records of the hours of operation of the emergency generator (VS-3). Said records shall be maintained on site or in a readily accessible off-site location maintained by the permittee for a period of five (5) years. Said records shall be readily available to the Director of the Division of Air Quality or his/her duly authorized representative for expeditious inspection and review. Any records submitted to the agency pursuant to a requirement of this permit or upon request by the Director shall be certified by a responsible official.
- 5.3.2. The permittee shall comply with all applicable recordkeeping requirements under NSPS for Stationary Compression Ignition Internal Combustion Engines specified in 40 CFR Part 60, Subpart IIII, and the National Emission Standards for Hazardous Air Pollutants (NESHAP) for Stationary Compression Ignition Internal Combustion Engines specified in 40 CFR Part 63, Subpart ZZZZ.

5.4. Reporting Requirements

- 5.4.1. See Facility-Wide Reporting Requirements Section 3.5 and all applicable reporting requirements under NSPS for Stationary Compression Ignition Internal Combustion Engines specified in 40 CFR Part 60, Subpart IIII, and the National Emission Standards for Hazardous Air Pollutants (NESHAP) for Stationary Compression Ignition Internal Combustion Engines specified in 40 CFR Part 63, Subpart ZZZZ.

DRAFT

6.0. Source-Specific Hazardous Air Pollutant Requirements (Natural Gas Dehydration Unit (VS-2) Not Subject to MACT Standards and being controlled by an Enclosed Combustor (CMB-1))

6.1. Limitations and Standards

6.1.1. **Maximum Throughput Limitation.** The maximum dry natural gas throughput to the TEG dehydration unit/still column (VS-2) shall not exceed 50 million standard cubic feet per day (mmscfd). Compliance with the Maximum Throughput Limitation shall be determined using a twelve month rolling total. A twelve month rolling total shall mean the sum of the monthly throughput at any given time during the previous twelve consecutive calendar months.

6.1.2. Maximum emissions from the enclosed combustion device (CMB-1) shall not exceed the following limits:

Pollutant	Maximum Hourly Emissions (lb/hr)	Maximum Annual Emissions (ton/year)
Volatile Organic Compounds	0.41	1.77
Nitrogen Oxides	1.61	7.05
Carbon Monoxide	0.35	5.92

6.1.3. Vapors that are being controlled by the enclosed combustion device (CMB-1) shall be routed to the enclosed combustion device at all times.

6.1.4. The enclosed combustion device (CMB-1) shall be operated with a flame present at all times, as determined by the methods specified in section 6.2.3 of this permit.

6.1.5. Enclosed combustion devices (CMB-1) shall be designed for and operated with no visible emissions as determined by the methods specified in permit section 6.3.1 except for either (a) or (b):

- a. periods not to exceed a total of one minute during any 15 minute period, determined on a monthly basis; or
- b. periods not to exceed a total of 2 minutes during any hour, determined on a quarterly basis if the enclosed combustion device installed was a model tested under § 60.5413(d) which meets the criteria in § 60.5413(d)(11).

6.1.6. Enclosed combustion device (CMB-1) shall be operated at all times when emissions may be vented to them.

6.1.7. To ensure compliance with permit section 6.1.6, the permittee shall monitor in accordance with section 6.2.3 of this permit.

6.1.8. The permittee shall operate and maintain the enclosed combustion device (CMB-1) according to the manufacturer's specifications for operating and maintenance requirements to maintain the guaranteed control efficiency.

6.1.9. Recycled reboilers controlling the Dehydrator Flash Tank shall be designed and operated in accordance with the following:

- a. The vapors/overheads from the flash tanks shall be routed through a closed vent system to the reboiler at all times when there is a potential that vapors (emissions) can be generated from the flash tank.
- b. The reboiler shall only be fired with vapors from the flash tank, and natural gas may be used as supplemental fuel.
- c. The vapors/overheads from the flash tank shall be introduced into the flame zone of the reboiler.

6.2. Monitoring Requirements

- 6.2.1. In order to demonstrate compliance with the requirements of 6.1.2, the permittee shall monitor the presence or absence of a pilot flame using a thermocouple or any other equivalent device, except during SSM events.
- 6.2.2. The permittee shall monitor the throughput of dry natural gas fed to the dehydration system on a monthly basis.
- 6.2.3. To demonstrate compliance with the pilot flame requirements of permit section 6.1.4, the permittee shall follow (i) and (ii), or (iii):
 - i. At a minimum frequency of once per calendar month, conduct visual inspections to confirm that the pilot is lit when vapors are being routed to the enclosed combustion device and that the continuous burning pilot flame is operating properly.
 - ii. For any absence of pilot flame, or other indication of smoking or improper equipment operation, you must ensure the equipment is returned to proper operation as soon as practicable after the event occurs. At a minimum, you must: (1) Check the air vent for obstruction. If an obstruction is observed, you must clear the obstruction as soon as practicable. (2) Check for liquid reaching the combustor.
 - iii. As an alternative, the permittee may meet the monitoring requirements of 6.2.1.
 - iv. The permittee is exempt from the pilot flame requirements of paragraphs (i) and (ii) of this section if the permittee installed an enclosed combustion device model that was tested under § 60.5413(d) which meets the criteria in § 60.5413(d)(11).

6.3. Testing Requirements

- 6.3.1. In order to demonstrate compliance with the opacity requirements of 6.1.5.b the permittee shall conduct a Method 22 opacity test for at least two hours. This test shall demonstrate no visible emissions are observed for more than a total of 5 minutes during any 2 consecutive hour period using 40CFR60 Appendix A Method 22. The permittee shall conduct this test within one (1) year of permit issuance or initial startup whichever is later. The visible emission checks shall determine the presence or absence of visible emissions. At a minimum, the observer must be trained and knowledgeable regarding the effects of background contrast, ambient lighting, observer position relative to lighting, wind, and the presence of uncombined water (condensing water vapor) on the visibility of emissions. This training may be obtained from written materials found in the References 1 and 2 from 40 CFR part 60, appendix A, Method 22 or from the lecture portion of 40 CFR part 60, appendix A, Method 9 certification course.

- 6.3.2. At such reasonable times as the Secretary may designate, the operator of any incinerator shall be required to conduct or have conducted stack tests to determine the particulate matter loading, by using 40 CFR Part 60, Appendix A, Method 5 or other equivalent U.S. EPA approved method approved by the Secretary, in exhaust gases. Such tests shall be conducted in such manner as the Secretary may specify and be filed on forms and in a manner acceptable to the Secretary. The Secretary may, at the Secretary's option, witness or conduct such stack tests. Should the Secretary exercise his or her option to conduct such tests, the operator will provide all the necessary sampling connections and sampling ports to be located in such manner as the Secretary may require, power for test equipment and the required safety equipment such as scaffolding, railings and ladders to comply with generally accepted good safety practices. The Secretary may conduct such other tests as the Secretary may deem necessary to evaluate air pollution emissions other than those noted above. [45CSR6 §§7.1 and 7.2]
- 6.3.3. In order to demonstrate compliance with 4.1.2, upon request of the Director, the permittee shall demonstrate compliance with the HAP emissions thresholds using GLYCalc Version 3.0 or higher. The permittee shall sample in accordance with GPA Method 2166 and analyze the samples utilizing the extended GPA Method 2286 as specified in the GRI-GLYCalc V4 Technical Reference User Manual and Handbook.

6.4. Recordkeeping Requirements

- 6.4.1. For the purpose of demonstrating compliance with section 6.1.5.c and 6.2.1, the permittee shall maintain records of the times and duration of all periods which the pilot flame was absent.
- 6.4.2. For the purpose of demonstrating compliance with the requirements set forth in sections 6.1.2 and 6.3.2., the permittee shall maintain records of testing conducted in accordance with 6.3.2.
- 6.4.3. The permittee shall document and maintain the corresponding records specified by the on-going monitoring requirements of 6.2 and testing requirements of 6.3.
- 6.4.4. For the purpose of demonstrating compliance with section 6.1.3.b, the permittee shall maintain records of the visible emission opacity tests conducted per Section 6.3.1.
- 6.4.5. For the purpose of demonstrating compliance with section 4.1.2, the permittee shall maintain a record of all potential to emit (PTE) HAP calculations for the entire affected facility. These records shall include the natural gas compressor engines and ancillary equipment.
- 6.4.6. The permittee shall maintain a record of the dry natural gas throughput through the dehydration system to demonstrate compliance with section 6.1.1.
- 6.4.7. All records required under Section 6.4 shall be maintained on site or in a readily accessible off-site location maintained by the permittee for a period of five (5) years. Said records shall be readily available to the Director of the Division of Air Quality or his/her duly authorized representative for expeditious inspection and review. Any records submitted to the agency pursuant to a requirement of this permit or upon request by the Director shall be certified by a responsible official.

6.5. Reporting Requirements

- 6.5.1 If permittee is required by the Director to demonstrate compliance with section 6.3.2, then the permittee shall submit a testing protocol at least thirty (30) days prior to testing and shall submit a notification of the testing date at least fifteen (15) days prior to testing. The permittee shall submit the testing results within sixty (60) days of testing and provide all supporting calculations and testing data.
- 6.5.2. Any deviation(s) from the allowable visible emission requirement for any emission source discovered during observations using 40CFR Part 60, Appendix A, Method 9 or 22 shall be reported in writing to the Director of the Division of Air Quality as soon as practicable, but in any case within ten (10) calendar days of the occurrence and shall include at least the following information: the results of the visible determination of opacity of emissions, the cause or suspected cause of the violation(s), and any corrective measures taken or planned.
- 6.5.3. Any deviation(s) from the enclosed combustor design and operation criteria in Section 6.1.8 shall be reported in writing to the Director of the Division of Air Quality as soon as practicable, but in any case within ten (10) calendar days of discovery of such deviation.

7.0. Source-Specific Requirements (Reboiler (VS-1))

7.1. Limitations and Standards

- 7.1.1. Maximum Design Heat Input. The maximum design heat input for the TEG Dehydration Unit Reboiler (VS-1) shall not exceed 1.0 MMBtu/hr.
- 7.1.2. No person shall cause, suffer, allow or permit emission of smoke and/or particulate matter into the open air from any fuel burning unit which is greater than ten (10) percent opacity based on a six minute block average.
[45CSR§2-3.1.]

7.2. Monitoring Requirements

- 7.2.1. At such reasonable times as the Secretary may designate, the permittee shall conduct Method 9 emission observations for the purpose of demonstrating compliance with Section 7.1.2. Method 9 shall be conducted in accordance with 40 CFR 60 Appendix A.

7.3. Testing Requirements

- 7.3.1. Compliance with the visible emission requirements of section 7.1.2 shall be determined in accordance with 40 CFR Part 60, Appendix A, Method 9 or by using measurements from continuous opacity monitoring systems approved by the Director. The Director may require the installation, calibration, maintenance and operation of continuous opacity monitoring systems and may establish policies for the evaluation of continuous opacity monitoring results and the determination of compliance with the visible emission requirements of section 7.1.2. Continuous opacity monitors shall not be required on fuel burning units which employ wet scrubbing systems for emission control.
[45CSR§2-3.2.]

7.4. Recordkeeping Requirements

- 7.4.1. The permittee shall maintain records of all monitoring data required by Section 7.2.1 documenting the date and time of each visible emission check, the emission point or equipment/source identification number, the name or means of identification of the observer, the results of the check(s), whether the visible emissions are normal for the process, and, if applicable, all corrective measures taken or planned. The permittee shall also record the general weather conditions (i.e. sunny, approximately 80°F, 6 - 10 mph NE wind) during the visual emission check(s). Should a visible emission observation be required to be performed per the requirements specified in Method 9, the data records of each observation shall be maintained per the requirements of Method 9.

7.5. Reporting Requirements

- 7.5.1. Any deviation(s) from the allowable visible emission requirement for any emission source discovered during observations using 40CFR Part 60, Appendix A, Method 9 or 22 shall be reported in writing to the Director of the Division of Air Quality as soon as practicable, but in any case within ten (10) calendar days of the occurrence and shall include at least the following information: the results of the visible determination of opacity of emissions, the cause or suspected cause of the violation(s), and any corrective measures taken or planned.

8.0. Source-Specific Requirements (Produced Fluids Tank, Tank-1)

8.1. Limitations and Standards

- 8.1.1. The permittee shall route all VOC and HAP emissions from the Produced Fluids Tank (Tank-1) to a vapor destruction unit (VDU-1), prior to release to the atmosphere. The vapor destruction unit shall be designed to achieve a minimum guaranteed control efficiency of 95% for volatile organic compound (VOC) and hazardous air pollutants (HAP) emissions.
- 8.1.2. *Operation and Maintenance of Air Pollution Control Equipment.* The permittee shall, to the extent practicable, install, maintain, and operate the vapor destruction unit (VDU-1) and associated monitoring equipment in a manner consistent with safety and good air pollution control practices for minimizing emissions, or comply with any more stringent limits set forth in this permit or as set forth by any State rule, Federal regulation, or alternative control plan approved by the Secretary.
[45CSR§13-5.11.]
- 8.1.3. The maximum annual throughput of product to the Produced Fluids storage tank (Tank-1) shall not exceed 2,649 gallons per year.
- 8.1.4. Emissions from the Produced Fluids storage tank (Tank-1) that are recovered and routed to the vapor destruction unit (VDU-1) shall be designed and operated as specified in the paragraphs (a) through (c).
- a. The cover and all openings on the cover (e.g., access hatches, sampling ports, pressure relief valves and gauge wells) shall form a continuous impermeable barrier over the entire surface area of the liquid in the storage vessel.
 - b. Each cover opening shall be secured in a closed, sealed position (e.g., covered by a gasketed lid or cap) whenever material is in the unit on which the cover is installed except during those times when it is necessary to use an opening as follows:
 - (i) To add material to, or remove material from the unit (this includes openings necessary to equalize or balance the internal pressure of the unit following changes in the level of the material in the unit);
 - (ii) To inspect or sample the material in the unit;
 - (iii) To inspect, maintain, repair, or replace equipment located inside the unit; or
 - (iv) To vent liquids, gases, or fumes from the unit through a closed-vent system designed and operated in accordance with the requirements 8.1.5 of this section to a control device.
 - c. Each thief hatch shall be weighted and properly seated. You must select gasket material for the hatch based on composition of the fluid in the storage vessel and weather conditions.
[45CSR§13-5.11]
- 8.1.5. The facility shall comply with the closed vent system requirements for the Produced Fluids Tank (Tank-1) as noted below.
- a. You must design the closed vent system to route all gases, vapors, and fumes emitted from the material in the Produced Fluids Tank (Tank-1) to the vapor destruction unit (VDU-1).
 - b. You must design and operate a closed vent system with no detectable emissions, as determined using olfactory, visual and auditory inspections.

- c. You must meet the requirements specified in paragraphs (i) and (ii) of this section if the closed vent system contains one or more bypass devices that could be used to divert all or a portion of the gases, vapors, or fumes from entering the control device or to a process.
 - (i) Except as provided in paragraph (ii) of this section, you must comply with either paragraph (A) or (B) of this section for each bypass device.
 - A. You must properly install, calibrate, maintain, and operate a flow indicator at the inlet to the bypass device that could divert the stream away from the control device or process to the atmosphere that sounds an alarm, or initiates notification via remote alarm to the nearest field office, when the bypass device is open such that the stream is being, or could be diverted away from the control device or process to the atmosphere.
 - B. You must secure the bypass device valve installed at the inlet to the bypass device in the non-diverting position using a car-seal or a lock-and-key type configuration.
 - (ii) Low leg drains, high point bleeds, analyzer vents, open-ended valves or lines, and safety devices are not subject to the requirements of paragraph (i) of this section.
- [45CSR§13-5.11]**

8.2. Monitoring Requirements

- 8.2.1. The permittee shall monitor the throughput to the vapor destruction unit (VDU-1) on a monthly basis.
- 8.2.2. To demonstrate compliance with section 8.1.1, the permittee shall monitor the vapor destruction unit (VDU-1) in accordance with the plans and specifications and manufacturer's recommendations.
- 8.2.3. To demonstrate compliance with the closed vent system requirements of Sections 8.1.4 and 8.1.5, the permittee shall:
 - a. Initial requirements. Conduct an initial visual, olfactory, and auditory inspection for defects that could result in air emissions within 180 days of start-up. Defects include, but are not limited to, visible cracks, holes, or gaps in piping; loose connections; liquid leaks; or broken or missing caps or other closure devices.
 - i. The annual inspection shall include the bypass inspection, conducted according to paragraph (c) of this section.
 - ii. In the event that a leak or defect is detected, you must repair the leak or defect as soon as practicable. Grease or another applicable substance must be applied to deteriorating or cracked gaskets to improve the seal while awaiting repair.
 - iii. Delay of repair of a closed vent system for which leaks or defects have been detected is allowed if the repair is technically infeasible without a shutdown, or if you determine that emissions resulting from immediate repair would be greater than the fugitive emission likely to result from delay of repair. You must complete repair of such equipment by the end of the next shutdown.
 - b. Continuous requirements. Conduct an annual visual, olfactory, and auditory inspection for defects that could result in air emissions. Defect include, but are not limited to, visible cracks, holes, or gaps in piping, loose connections; liquid leaks; or broken or missing caps or other closure devices.

- i. The annual inspection shall be conducted within 365 calendar days from the date of the previous inspection or earlier.
 - ii. The annual inspection shall include the bypass inspection, conducted according to paragraph (c) of this section.
- c. Bypass inspection. Visually inspect the bypass valve during the initial and annual inspection for the presence of the car seal or lock-and-key type configuration to verify that the valve is maintained in the non-diverting position to ensure that the vent stream is not diverted through the bypass device. If an alternative method is used, conduct the inspection of the bypass as described in the operating procedures.
- d. Unsafe to inspect requirements. You may designate any parts of the closed vent system as unsafe to inspect if the requirements in paragraphs (i) and (ii) of this section are met. Unsafe to inspect parts are exempt from the inspection requirements of paragraphs (a) and (b) of this section.
 - i. You determine that the equipment is unsafe to inspect because inspecting personnel would be exposed to an imminent or potential danger as a consequence of complying with the requirements.
 - ii. You have a written plan that requires inspection of the equipment as frequently as practicable during safe-to-inspect times.
- e. Difficult to inspect requirements. You may designate any parts of the closed vent system as difficult to inspect, if the requirements in paragraphs (i) and (ii) of this section are met. Difficult to inspect parts are exempt from the inspection requirements of paragraphs (a) and (b) of this section.
 - i. You determine that the equipment cannot be inspected without elevating the inspecting personnel more than 2 meters above a support surface.
 - ii. You have a written plan that requires inspection of the equipment at least once every 5 years.

[45CSR§13-5.11]

8.3. Recordkeeping Requirements

- 8.3.1. All records required under Section 8.3 shall be maintained on site or in a readily accessible off-site location maintained by the permittee for a period of five (5) years. Said records shall be readily available to the Director of the Division of Air Quality or his/her duly authorized representative for expeditious inspection and review. Any records submitted to the agency pursuant to a requirement of this permit or upon request by the Director shall be certified by a responsible official.
- 8.3.2. *Record of Maintenance of VDU.* The permittee shall maintain accurate records of the vapor destruction unit (VDU-1) equipment inspection and/or preventative maintenance procedures.
- 8.3.3. *Record of Malfunctions of VDU.* The permittee shall maintain records of the occurrence and duration of any malfunction or operational shutdown of the vapor destruction unit (VDU-1) during which excess emissions occur. For each such case, the following information shall be recorded:
 - a. The equipment involved.
 - b. Steps taken to minimize emissions during the event.

- c. The duration of the event.
- d. The estimated increase in emissions during the event.

For each such case associated with an equipment malfunction, the additional information shall also be recorded:

- e. The cause of the malfunction.
 - f. Steps taken to correct the malfunction.
 - g. Any changes or modifications to equipment or procedures that would help prevent future recurrences of the malfunction.
- 8.3.4. To demonstrate compliance with section 8.1.3, the permittee shall maintain a record of the throughput for the storage tank (Tank-1) on a monthly and rolling twelve month total. Said records shall be maintained on site or in a readily accessible off-site location maintained by the permittee for a period of five (5) years. Said records shall be readily available to the Director of the Division of Air Quality or his/her duly authorized representative for expeditious inspection and review. Any records submitted to the agency pursuant to a requirement of this permit or upon request by the Director shall be certified by a responsible official.
- 8.3.5. The permittee shall maintain a copy all design records of the process, maintenance records of equipment and any downtime hours associated with the vapor destruction unit (VDU-1).
- 8.3.6. To demonstrate compliance with the closed vent monitoring requirements, the following records shall be maintained.
- i. The initial compliance requirements;
 - ii. Each annual visual inspection conducted to demonstrate continuous compliance, including records of any repairs that were made as results of the inspection;
 - iii. Bypass requirements.
 - a. Each inspection or each time the key is checked out or a record each time the alarm is sounded;
 - b. Each occurrence that the control device was bypassed. If the device was bypassed, the records shall include the date, time, and duration of the event and shall provide the reason the event occurred. The record shall also include the estimate of emissions that were released to the environment as a result of the bypass.
 - iv. Any part of the system that has been designated as “unsafe to inspect” in accordance with 8.2.3.d or “difficult to inspect” in accordance with 8.2.3.e.
- [45CSR§13-5.11]**

8.4. Reporting Requirements

- 8.4.1. Upon request by the Director, the permittee shall report deviations within a requested time from of any occurrences when the control device was operated outside of the parameters defined in the monitoring plan.
- 8.4.2. The permittee shall notify the Director of any downtime of the VDU in excess of 5%, based on the 12 month rolling total, in writing to the Director of the Division of Air Quality as soon as practicable, but within ten (10) calendar days of the discovery and shall include, at a minimum, the following information: the dates and durations of each downtime event, the cause or suspected causes for each downtime event, any corrective measures taken or planned for each downtime event.

DRAFT

9.0. Source-Specific Requirements (Product Loadout Rack, BL-1)

9.1. Limitations and Standards

- 9.1.1. The permittee shall route all VOC and HAP emissions from the Product Loadout Rack (BL-1) to a vapor destruction unit (VDU-1), prior to release to the atmosphere. The vapor destruction unit (VDU-1) shall be designed to achieve a minimum guaranteed control efficiency of 95% for volatile organic compound (VOC) and hazardous air pollutants (HAP) emissions.
- 9.1.2. *Operation and Maintenance of Air Pollution Control Equipment.* The permittee shall, to the extent practicable, install, maintain, and operate the vapor destruction unit (VDU-1) and associated monitoring equipment in a manner consistent with safety and good air pollution control practices for minimizing emissions, or comply with any more stringent limits set forth in this permit or as set forth by any State rule, Federal regulation, or alternative control plan approved by the Secretary.
[45CSR§13-5.11.]
- 9.1.3. The maximum quantity of condensate/produced water that shall be loaded shall not exceed 2,649 gallons per year. Compliance with the Maximum Yearly Operation Limitation shall be determined using a twelve month rolling total. A twelve month rolling total shall mean the sum of the hours of operation at any given time during the previous twelve consecutive calendar months.
- 9.1.4. The Product Loadout Rack shall be operated in accordance with the plans and specifications filed in Permit Application R13-3208.
- 9.1.5. Emissions from the Product Loadout Rack (BL-1) that are recovered and routed to the Vapor Destruction Unit (VDU-1) shall be designed and operated as specified in the paragraphs (a) through (c).
- a. The cover and all openings on the cover (e.g., access hatches, sampling ports, pressure relief valves and gauge wells) shall form a continuous impermeable barrier over the entire surface area of the liquid in the storage vessel.
 - b. Each cover opening shall be secured in a closed, sealed position (e.g., covered by a gasketed lid or cap) whenever material is in the unit on which the cover is installed except during those times when it is necessary to use an opening as follows:
 - (i) To add material to, or remove material from the unit (this includes openings necessary to equalize or balance the internal pressure of the unit following changes in the level of the material in the unit);
 - (ii) To inspect or sample the material in the unit;
 - (iii) To inspect, maintain, repair, or replace equipment located inside the unit; or
 - (iv) To vent liquids, gases, or fumes from the unit through a closed-vent system designed and operated in accordance with the requirements 9.1.6 of this section to a control device.
 - c. Each thief hatch shall be weighted and properly seated. You must select gasket material for the hatch based on composition of the fluid in the storage vessel and weather conditions.
[45CSR§13-5.11]

- 9.1.6. The facility shall comply with the closed vent system requirements for the Product Loadout Rack (BL-1) as noted below.
- a. You must design the closed vent system to route all gases, vapors, and fumes emitted from the material in the Product Loadout Rack (BL-1) to the vapor destruction unit (VDU-1).
 - b. You must design and operate a closed vent system with no detectable emissions, as determined using olfactory, visual and auditory inspections.
 - c. You must meet the requirements specified in paragraphs (i) and (ii) of this section if the closed vent system contains one or more bypass devices that could be used to divert all or a portion of the gases, vapors, or fumes from entering the control device or to a process.
 - (i) Except as provided in paragraph (ii) of this section, you must comply with either paragraph (A) or (B) of this section for each bypass device.
 - A. You must properly install, calibrate, maintain, and operate a flow indicator at the inlet to the bypass device that could divert the stream away from the control device or process to the atmosphere that sounds an alarm, or initiates notification via remote alarm to the nearest field office, when the bypass device is open such that the stream is being, or could be diverted away from the control device or process to the atmosphere.
 - B. You must secure the bypass device valve installed at the inlet to the bypass device in the non-diverting position using a car-seal or a lock-and-key type configuration.
 - (ii) Low leg drains, high point bleeds, analyzer vents, open-ended valves or lines, and safety devices are not subject to the requirements of paragraph (i) of this section.
- [45CSR§13-5.11]

9.2. Monitoring Requirements

- 9.2.1. The permittee shall monitor the throughput to the vapor destruction unit (VDU-1) on a monthly basis.
- 9.2.2. To demonstrate compliance with section 9.1.1, the permittee shall monitor the vapor destruction unit (VDU-1) in accordance with the plans and specifications and manufacturer's recommendations.
- 9.2.3. To demonstrate compliance with the closed vent system requirements of Sections 9.1.5 and 9.1.6, the permittee shall:
- a. Initial requirements. Conduct an initial visual, olfactory, and auditory inspection for defects that could result in air emissions within 180 days of start-up. Defects include, but are not limited to, visible cracks, holes, or gaps in piping; loose connections; liquid leaks; or broken or missing caps or other closure devices.
 - i. The annual inspection shall include the bypass inspection, conducted according to paragraph (c) of this section.
 - ii. In the event that a leak or defect is detected, you must repair the leak or defect as soon as practicable. Grease or another applicable substance must be applied to deteriorating or cracked gaskets to improve the seal while awaiting repair.
 - iii. Delay of repair of a closed vent system for which leaks or defects have been detected is allowed if the repair is technically infeasible without a shutdown, or if you determine that

emissions resulting from immediate repair would be greater than the fugitive emission likely to result from delay of repair. You must complete repair of such equipment by the end of the next shutdown.

- b. Continuous requirements. Conduct an annual visual, olfactory, and auditory inspection for defects that could result in air emissions. Defect include, but are not limited to, visible cracks, holes, or gaps in piping, loose connections; liquid leaks; or broken or missing caps or other closure devices.
 - i. The annual inspection shall be conducted within 365 calendar days from the date of the previous inspection or earlier.
 - ii. The annual inspection shall include the bypass inspection, conducted according to paragraph (c) of this section.
- c. Bypass inspection. Visually inspect the bypass valve during the initial and annual inspection for the presence of the car seal or lock-and-key type configuration to verify that the valve is maintained in the non-diverting position to ensure that the vent stream is not diverted through the bypass device. If an alternative method is used, conduct the inspection of the bypass as described in the operating procedures.
- d. Unsafe to inspect requirements. You may designate any parts of the closed vent system as unsafe to inspect if the requirements in paragraphs (i) and (ii) of this section are met. Unsafe to inspect parts are exempt from the inspection requirements of paragraphs (a) and (b) of this section.
 - i. You determine that the equipment is unsafe to inspect because inspecting personnel would be exposed to an imminent or potential danger as a consequence of complying with the requirements.
 - ii. You have a written plan that requires inspection of the equipment as frequently as practicable during safe-to-inspect times.
- e. Difficult to inspect requirements. You may designate any parts of the closed vent system as difficult to inspect, if the requirements in paragraphs (i) and (ii) of this section are met. Difficult to inspect parts are exempt from the inspection requirements of paragraphs (a) and (b) of this section.
 - i. You determine that the equipment cannot be inspected without elevating the inspecting personnel more than 2 meters above a support surface.
 - ii. You have a written plan that requires inspection of the equipment at least once every 5 years.

[45CSR§13-5.11]

9.3. Recordkeeping Requirements

- 9.3.1. All records required under Section 9.3 shall be maintained on site or in a readily accessible off-site location maintained by the permittee for a period of five (5) years. Said records shall be readily available to the Director of the Division of Air Quality or his/her duly authorized representative for expeditious inspection and review. Any records submitted to the agency pursuant to a requirement of this permit or upon request by the Director shall be certified by a responsible official.
- 9.3.2. *Record of Maintenance of VDU.* The permittee shall maintain accurate records of the vapor destruction unit (VDU-1) equipment inspection and/or preventative maintenance procedures.

9.3.3. *Record of Malfunctions of VDU.* The permittee shall maintain records of the occurrence and duration of any malfunction or operational shutdown of the vapor destruction unit (VDU-1) during which excess emissions occur. For each such case, the following information shall be recorded:

- a. The equipment involved.
- b. Steps taken to minimize emissions during the event.
- c. The duration of the event.
- d. The estimated increase in emissions during the event.

For each such case associated with an equipment malfunction, the additional information shall also be recorded:

- e. The cause of the malfunction.
- f. Steps taken to correct the malfunction.
- g. Any changes or modifications to equipment or procedures that would help prevent future recurrences of the malfunction.

9.3.4. To demonstrate compliance with section 9.1.3, the permittee shall maintain a record of the throughput for the product loadout rack (BL-1) on a monthly and rolling twelve month total. Said records shall be maintained on site or in a readily accessible off-site location maintained by the permittee for a period of five (5) years. Said records shall be readily available to the Director of the Division of Air Quality or his/her duly authorized representative for expeditious inspection and review. Any records submitted to the agency pursuant to a requirement of this permit or upon request by the Director shall be certified by a responsible official.

9.3.5. The permittee shall maintain a copy all design records of the process, maintenance records of equipment and any downtime hours associated with the vapor destruction unit (VDU-1).

9.3.6. To demonstrate compliance with the closed vent monitoring requirements, the following records shall be maintained.

- i. The initial compliance requirements;
- ii. Each annual visual inspection conducted to demonstrate continuous compliance, including records of any repairs that were made as results of the inspection;
- iii. Bypass requirements.
 - a. Each inspection or each time the key is checked out or a record each time the alarm is sounded;
 - b. Each occurrence that the control device was bypassed. If the device was bypassed, the records shall include the date, time, and duration of the event and shall provide the reason the event occurred. The record shall also include the estimate of emissions that were released to the environment as a result of the bypass.

- iv. Any part of the system that has been designated as “unsafe to inspect” in accordance with 9.2.3.d or “difficult to inspect” in accordance with 9.2.3.e.

[45CSR§13-5.11]

9.4. Reporting Requirements

- 9.4.1. Upon request by the Director, the permittee shall report deviations within a requested time from of any occurrences when the control device was operated outside of the parameters defined in the monitoring plan.
- 9.4.2. The permittee shall notify the Director of any downtime of the VDU in excess of 5%, based on the 12 month rolling total, in writing to the Director of the Division of Air Quality as soon as practicable, but within ten (10) calendar days of the discovery and shall include, at a minimum, the following information: the dates and durations of each downtime event, the cause or suspected causes for each downtime event, any corrective measures taken or planned for each downtime event.

DRAFT

CERTIFICATION OF DATA ACCURACY

I, the undersigned, hereby certify that, based on information and belief formed after reasonable inquiry, all information contained in the attached _____, representing the period beginning _____ and ending _____, and any supporting documents appended hereto, is true, accurate, and complete.

Signature¹

(please use blue ink)

Responsible Official or Authorized Representative

Date

Name & Title

(please print or type)

Name

Title

Telephone No. _____

Fax No. _____

¹ This form shall be signed by a "Responsible Official." "Responsible Official" means one of the following:

- a. For a corporation: The president, secretary, treasurer, or vice-president of the corporation in charge of a principal business function, or any other person who performs similar policy or decision-making functions for the corporation, or a duly authorized representative of such person if the representative is responsible for the overall operation of one or more manufacturing, production, or operating facilities applying for or subject to a permit and either:
 - (i) the facilities employ more than 250 persons or have a gross annual sales or expenditures exceeding \$25 million (in second quarter 1980 dollars), or
 - (ii) the delegation of authority to such representative is approved in advance by the Director;
- b. For a partnership or sole proprietorship: a general partner or the proprietor, respectively;
- c. For a municipality, State, Federal, or other public entity: either a principal executive officer or ranking elected official. For the purposes of this part, a principal executive officer of a Federal agency includes the chief executive officer having responsibility for the overall operations of a principal geographic unit of the agency (e.g., a Regional Administrator of U.S. EPA); or
- d. The designated representative delegated with such authority and approved in advance by the Director.